

105.001

Bride de serrage en métal 18x4mm
pour câble rond Ø maxi 8.5mm
écartement 13 mm, vis M2.5x8

Zugentlastungsbride Metal 18x4mm
für Rundkabel Ø maxi 8.5mm
Lochdistanz 13 mm, Schrauben M2.5x8



303.001 Interrupteur lumineux blanc Leuchtender Schalter weiss

303.002 Interrupteur lumineux noir Leuchtender Schalter schwarz

Rating (1 pole):

16 (6) A 250 V ~
10 (4) A 250 V ~+++
10 (4) A 400 V ~
20 A 125 V AC 1/4 Hp
(UL/CSA)
15 A 250 V AC 1/4 Hp
(ULCSA)

Temperature rating T °C:

T 125
UL/CSA: T 65 (T 105)

Mechanical life:

300.000 cycles



6,3 x 0,8 mm



303.010 Interrupteur lumineux blanc Leuchtender Schalter weiss

303.011 Interrupteur lumineux noir Leuchtender Schalter schwarz

Rating (2 pole):

16 (6) A 250 V ~
10 (4) A 250 V ~+++
10 (4) A 400 V ~
20 A 125 V AC 1/4 Hp
(UL/CSA)
15 A 250 V AC 1/4 Hp
(ULCSA)

Temperature rating T °C:

T 125
UL/CSA: T 65 (T 105)

Mechanical life:

300.000 cycles



6,3 x 0,8 mm

